

DR200/HE Holter and Event Recorder

Meets EC-38 standard

14-day Holter capability

Multiple Language capability

Ergonomic Design

Proven reliability

Maximize Holter and Event reimbursements

Reduce artifact with low-cost, shielded cables

Pacemaker detection standard

Combination
Holter and
Event

Industry-leading 3-year warranty



The DR200/HE is the industry's first combination 14-day Holter plus Event recorder. It can be deployed to a patient in either Holter or Event mode. In Holter mode with a single, fully charged AA battery and a 1GigaByte data card, the unit can operate as a 14-day Holter. When the DR200/HE is combined with Holter LX Analysis and LX Event software, you have the flexibility to use your capital equipment in the most efficient manner and you've increased the probability of

capturing elusive cardiac events. It is the best solution for your practice and the best solution for your patient, which is another good combination!

The DR200/HE blends the features of the DR200/E "Tel-a-heart" Event recorder (see the DR200/E Data Sheet for complete details) and the established technology of the tried-and-true "workhorse" DR180+ Holter in a single, compact, rugged unit. New advanced DSP hardware and specially designed signal processing algorithms squeeze every milli-watt out of the battery to establish a new price-performance benchmark in ambulatory cardiac monitors. The unit is approximately one-half the size and weight of the DR180+, has smaller cable profiles for patient comfort, yet adds more functionality and convenience.

When deployed as a Holter, the DR200/HE has either 3-, 5- or 7-lead cables. When deployed as a Tel-a-heart Event monitor, it uses a 2- or 3-lead cable. The DR200/HE kit includes Holter cable, pouch, belt clip, removable media memory card, Operator's Manual and Hook-up Guide.

At NorthEast, we are advancing Holter technology - smaller in size, lower in cost, compatible with all levels of LX Analysis, the industry's best warranty of 3 years, with an optional extension to 5 or more years – the DR200/HE is the technology and quality leader in the industry today.

For more information on the DR200/HE combination Holter and Event Recorder, please contact NorthEast or read on for more details.

DR200/HE[™]Features

◆Meets EC-38 standard

Meets applicable sections of ANSI/AAMI ED38-1994 "Ambulatory Electrocardiographs."

◆14 day Holter capability captures infrequent cardiac events

Efficient low-power design and robust LX Analysis software, version 5.2 or greater, now makes it possible to use the DR200/HE in Holter-mode over a 14-day period to capture infrequent cardiac events without the need to rely on patient interaction or automatic detection.

◆Multiple Language Capability

Select from English, Danish, Finnish, French, German, Italian, Polish, Portuguese and Spanish.

◆Ergonomic design

Large, easy view LCD (liquid crystal display) screen, soft-keys and a very simple user interface make the unit exceptionally easy to use.

◆Proven reliability

Built on the platform of the reliable DR180+, there are thousands of Holter units deployed worldwide. Real-world experience is designed into every unit.

◆Maximize Holter and Event reimbursements

Our system allows your office to "capture" reimbursement for all components of CPT (Current Procedural Terminology) allowed for Holter and Event. Removable digital storage memory (compact flash) allows for rapid re-deployment of the unit to the next patient.

◆Reduce artifact with low cost, shielded cables

Shielded cables provide better signal integrity and noise immunity. Our cables are carefully shielded and impedance matched and provide better SNR than any other cable on the market. Low cost cables drive down the total cost of ownership.

◆Pacemaker detection standard

The conflicting requirements for signal sensitivity (wide bandwidth and high sample rate) and long battery life have been uniquely resolved to provide the most accurate diagnostic information.

◆Industry-leading 3-year warranty

These units are built-to-last. Our field return rate is proven to be so low that we can offer the industry's longest warranty -- and then extend that to 5 or more years to add even more value to your investment.

◆Maximize good quality recording cycles

Checks battery state and lead hook-up quality, date and Patient ID on LCD prior to deployment. No mix-ups with patient data because patient ID is encoded on memory card.

All digital recording

Reliable digital technology is used throughout, enhancing service life and lowering total cost of ownership.

◆ Compatible with Holter LX® Analysis and LX Event software

The DR200 Holter recorder is compatible with 5.2 or newer versions of Holter LX Analysis.

(See DR200/E Data Sheet for additional, event-specific features.)

FDA K061293, K070014

NB: In the U.S.A., Federal Law restricts devices to sale by or on the order of a physician. For in vitro diagnostic use. Not intended to replace real-time telemetry monitoring for patients suspected of having life-threatening arrhythmias.

August 2011



DR200/HE Specifications

Recording duration:

14 days with alkaline battery

Recording bandwidth:

0.05 - 70 Hz

Resolution:

12-bit, 12.50 µV/LSB

Sampling rate:

180 samples/second

Dimensions:

8.6 cm x 6.0 cm x 2.0 cm (3.9 in x 2.4 in x 0.8 in)

Weight:

99.3 grams (3.5 oz), with battery 70.9 (2.5 oz), without battery

Power:

1 AA battery: alkaline, NiMH rechargeable, or lithium

Storage capacity:

32 MB - 1 GB SD Flashcard

Distributed by:



782 Heidelberg Road FAIRFIELD VIC 3078 AUSTRALIA Phone: +61 3 9497 3633 Fax: +61 3 9497 3188

> E-mail: medical@machineryforum.com.au www.mfmedical.net.au